Address:

Grant: URP20 Home 5
Preparer: Carlis P. Sweat

TOWN OF	Visit the Southern Pines Planning Department at 180 SW Broad St., Southern Pines, NC 28327 to obtain permits for the work performed on	
SOUTHERN	this home.	
PINES	The following permits are required:	Not a Bid
PERMITTING	-Building-Plumbing-Insulation-	Item
REQUIREMENTS	Please contact the Southern Pines Permitting office (910-692-4003) directly for permits & permit costs.	
LEAD BASE	This is a pre-1978 built home. Safe Work Practices (SWP) and Renovate, Repair, and Paint (RR&P) techniques must be used when performing	Not a Bid
PAINT	work on this home.	Item
REQUIREMENTS FOR ALL WORK WRITEUPS	*Work on any item specified in this write-up is to be performed to code and will be inspected & approved as such. This is to apply in all instances and regardless of whether the specification states to perform work "to code." When a contractor or subcontractors are uncertain as to code requirements or where it appears the specification contradicts code the Community Development Staff shall be contacted before work is performed.  * All materials used in connection with this Work Write-Up are to be new, of first quality and without defects - unless stated otherwise in the Work Write-Up or pre-approved by Community Development Staff.  **Comparable substitutes for items specified in this Work Write-Up may be used provided the homeowner, contractor, and Community Development Staff are in agreement and this agreement is reduced to writing and signed by all three parties.  **Any changes in the Work Write-Up shall be pre-approved by the homeowner, contractor, and Community Development Staff and once all parties are in agreement then this agreement shall be reduced to writing and signed by all three parties.  **Contractor is to allow the homeowner a minimum of three choices of color or style for all material selections specified to be replaced in the Work Write-Up.  **Warranties for work performed and all material items installed on a home (e.g. roofing, vinyl siding, heat pump, appliances, termite inspection, etc.) will be provided to Community Development Staff prior to final payment being made for work performed under this contract.  **At the preconstruction meeting, Contractors will be provided with a Release of Liens that will need to be signed by all subcontractors prior to final payment is made for work performed under this contract.  **Contractors and their Subcontractors shall schedule working hours between 8:00am and 6:00pm Monday through Friday. Requests to work on weekends and before or after these hours must be approved by the homeowner. The Contractor is responsible for informing Community Development Staf	Not a Bid Item

Locatio	<u>on</u>	<u>Item</u>	<u>Specification</u>	<u>Material</u>	<u>Labor</u>	<u>Total</u>
EXTERI	OR			<u>Cost</u>	<u>Cost</u>	<u>Price</u>
1.	CRAWLSPACE	Girder Support	Temporarily support middle third of floor joists at four load bearing points			
1.	CNAWLSI ACL	Prep	removing pressure on two center girders in preparation of foundation pier			
		1100	work. Remove four (4) old CMU piers.			
		Footings	Dig four (4)-16"x24"x10" deep footings in old pier positions moving locations			
			slightly (+/-4-5") to place existing girders onto middle of pier points. Pour			
			3,000 psi concrete into holes.			
		Pier	Dry stack different dimensional CMU's and/or brick 8"x16" to attain required			
		Construction	pier height level to original foundation height (approximately 24" tall). Finish			
			cap shall be of solid material or filled with cement. Parge all four sides of piers			
			with a fiber reinforced Surewall® Surface Bonding Cement product.			
		Girder Straps	Re-set girders onto piers after pulling them back into upright positions as two			
			(2) double 2x8's are installed between both girders at both center pier			
			positions, and strapping all of this together using 16-gauge Simpson Strong			
			Tie™ metal strap nailed up outer sides of girders and across entire bottom of			
			doubles between girders.			
2.	PORCH STEP	Handrail	Remove existing step railing and first one foot of horizontal handrail only.			
	RAIL		Install wrought iron railing up steps and over to first corner post			
			(approximately 6lf). Secure bottom of railing into ground with concrete mix,			
			bolt upper step rail corner to porch surface and weld short horizontal railing			
			to existing corner post. Extend top rail of step handrail section past bottom post one foot (12").			
INTERI	OR.		post one loot (12 ).			
3.	BATHROOM	Prep	Remove all wall materials from around tub down to the studs. Remove			
]	DATIMOON	1100	window trim kit, baseboard and shoe moulding covering wallboard finished			
			walls. Remove all wallboard wainscot paneling and wallpaper from entire			
			bathroom wall areas. Remove toilet and save for re-use.			
		Insulation	Insulate exterior end shower wall with R-15 insulation and vapor barrier.			
		Blocking	Install blocking into back wall of tub for grab bar placement using 2x material.			
		Shower	Install a Delta <sup>®</sup> Classic Chrome single lever faucet and a Delta <sup>®</sup> handheld			
		Faucet	shower head with stainless braided line onto a mounting slide bar (or a CD			
			Staff pre-approved equals). Install a complete drain assembly. Include all			
			supply and DWV lines associated with installation of this unit. Home has			
			copper supply and cast-iron drain lines.			
		Toilet	Reset existing toilet. Replace cut-off valve.			
		Drywall	Install water resistant drywall around tub walls up to ceiling angles. Tape,			
			bed, skim, and sand drywall ready for paint. Install an 8' corner bead onto			

	bathtub corner framing. Skim coat and sand all walls where wallpaper was	
	removed and make ready for paint.	
Tub Surround	Install a Swanstone® Veritek® white panel kit shower tub wall surround, 60-in	
	x 30-in (HOME DEPOT Store SKU SO #10009 Model #GN-58.010 or a CD Staff	
	preapproved equal). Prime drywall prior to gluing panels. Use an adhesive	
	silicone caulk and glue.	
Step/Door	Install a CleanCut® Safety Step and door onto middle third of bathtub outside	
	rim. Product and ordering information can be found at	
	https://cleancutbath.com/product/cleancut-door/	
Grab Bars	Mount one (1)- 2' stainless steel 1¼" peened grab bar on corner outside of	
	shower and one (1) 3' stainless steel 1¼" peened grab bar mounted at an	
	angle along back wall (on an approximate 30° angle).	
Underlayment	Install one layer of ¼" lauan plywood over entire floor area (approximately	
Sinderiayinene	40sf).	
Flooring	Install approximately <u>40</u> sf of SMARTCORE Vinyl Plank flooring (LOWES or CD	
Tioding	Staff pre-approved equal) over the entire bathroom floor. Install transition	
	strip/carpet bar.	
Trim	Install matching baseboard and shoe moulding onto all bathroom walls less	
	closet (apprx. twenty linear feet <u>20</u> If of baseboard and twenty six linear feet	
	· · · · · · · · · · · · · · · · · · ·	
	26lf of shoe. Re-trim a 2/8-3/2 window w/ window stop, 2¼" casing, stool and	
Point	apron.	
Paint	Paint all new finished walls and trim with a coat of primer. Paint all walls,	
	casing, base and shoe with two coats of matching finish and color.	

Material Cost Total:	Labor Cost Total:	Grand Total:	
Respectfully submitted by:			
Contractor Name (PRINT):		Tax ID Number:	_
Signature:		Phone Number:	
Signature:		Thore Number.	
Date:			